

DUBUQUE, IOWA

AL-923 (FAA)

25275

WAAS CH 62807 W36A	APP CRS 357°	Rwy Ldg 6327 TDZE 1048 Apt Elev 1077
--	------------------------	---

RNAV (GPS) RWY 36
DUBUQUE RGNL (DBQ)

RNP APCH.



For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 46°C. Baro-VNAV and VDP NA when using Monticello altimeter setting. When local altimeter setting not received, use Monticello altimeter setting and increase all DA 88 feet and all MDA 100 feet, increase LNAV/VNAV all Cats, LNAV Cats C and D and Circling Cat C visibility ¼ mile. For inop MALSR when using Monticello altimeter setting, increase LPV all Cats visibility to RVR 5000.

*RVR 1800 authorized with use of FD or AP or HUD to DA, NA when using Monticello altimeter setting.




MALSR



MISSED APPROACH:
Climb to 3000 direct
WABKU and via 314°
track to CASSY and hold.

ATIS 127.25	CHICAGO CENTER 133.95 281.4	DUBUQUE TOWER ★ 119.5 (CTAF) 0 254.4	GND CON 121.8	UNICOM 122.95
-----------------------	---------------------------------------	--	-------------------------	-------------------------

MISSED APCH FIX



3000 ↑	WABKU ✱	314° tr	CASSY △	VGS1 and RNAV glidepath not coincident (VGS1 Angle 3.00/TCH 51).				4 NM Holding Pattern
* LNAV only.				LATCI	DIVGE			
				GP 3.00° TCH 50				
CATEGORY	A		B		C		D	
LPV DA#	1248/24		200 (200-½)					
LNAV/VNAV DA	1525/60		477 (500-1¼)					
LNAV MDA	1480/24	432 (500-½)	1480/40 432 (500-¾)	1480/50 432 (500-1)				
CIRCLING	1580-1	503 (600-1)	1600-1½ 523 (600-1½)	1800-2¼ 723 (800-2¼)				

DUBUQUE, IOWA
Orig-B 10OCT19

42°24'N-90°43'W

DUBUQUE RGNL (DBQ)

RNAV (GPS) RWY 36

NC-3, 01 OCT 2026 to 29 OCT 2026