



WAAS CH 40435 W19A	APP CRS 188°	Rwy Ldg TDZE 736 Apt Elev 742
--	------------------------	---

RNAV (GPS) RWY 19
CHICAGO/ROCKFORD INTL (RFD)

RNP APCH - GPS.				MISSED APPROACH: Climb to 2500 direct CONAN and hold.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C.				
 ASR	ATIS 127.6	ROCKFORD APP CON 121.0 327.0	ROCKFORD TOWER 118.1 290.375	GND CON 121.9 290.375



2500 CONAN		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).		4 NM Holding Pattern	
JUNUP 1.6 NM to RW19		CAGRA 2500		WAGET	
1 NM to RW19		1280		188°	
1 NM		0.6 NM		3.8 NM	
1 NM		0.6 NM		7 NM	
CATEGORY	A	B	C	D	
LPV DA	936-3/4 200 (200-3/4)				
LNAV/VNAV DA	1039-7/8 303 (300-7/8)				
LNAV MDA	1120-1	384 (400-1)	1120-1 1/2	384 (400-1 1/2)	
CIRCLING	1220-1 478 (500-1)	1280-1 538 (600-1)	1320-1 1/2 578 (600-1 1/2)	1460-2 1/4 718 (800-2 1/4)	