



WAAS CH 90509 W14A	APP CRS 144°	Rwy Ldg TDZE 1169 Apt Elev 1189
--	------------------------	---

RNAV (GPS) Y RWY 14L

GRANT COUNTY INTL (MWH)

RNP APCH. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 36°C. ▲ Baro-VNAV and VDP NA when using Ephrata altimeter setting. When local altimeter setting not received, use Ephrata altimeter setting; increase all DA 36 feet and all MDA 40 feet, increase LNAV/VNAV visibility all Cats ⅓ SM, LNAV Cats C and D and Circling Cat D ¼ SM.	MISSED APPROACH: Climb to 4000 direct HEDBI and on track 124° to UPBOB and hold.
--	--

ATIS 119.05	GRANT COUNTY APP CON ★ 126.4 379.95	GRANT COUNTY TOWER ★ 118.25 (CTAF) 0 257.8 (E) 128.0 257.8 (W)	GND CON 121.9	UNICOM 122.95
-----------------------	---	--	-------------------------	-------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).			
4 NM Holding Pattern	JUKRI	ILARE	4000 HEDBI tr 124° UPBOB
4000 ← 324°	144° →	144° →	*LNAV only.
GP 3.00° TCH 52	3000	3000	*1.1 NM to RW14L
6.4 NM 3.8 NM 0.7 1.1 NM			
CATEGORY	A	B	C
LPV DA	1369-¾	200 (200-¾)	
LNAV/VNAV DA	1436-⅞	267 (300-⅞)	
LNAV MDA	1580-1 411 (400-1)	1580-1½ 411 (400-1½)	
CIRCLING	1660-1 471 (500-1)	1680-1½ 491 (500-1½)	1820-2 631 (700-2)