

WAAS CH 99330 W16A	APP CRS 158°	Rwy Ldg TDZE 213 Apt Elev 213
--	------------------------	---

RNAV (GPS) RWY 16


TRENTON MERCER (TTN)

▼ Night Landing: Rwy 34 operational VGSI required, remain on or above VGSI glidepath until threshold. Baro-VNAV NA when using Northeast Philadelphia altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.


▲ Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received use Northeast Philadelphia altimeter setting; increase LPV DA to 510 feet and all Cats visibility ¾ SM, LNAV/VNAV DA to 576 feet; increase all MDA 60 feet and LNAV Cat C/D visibility ¾ SM and Circling Cat C visibility ½ SM.

MISSED APPROACH:
Climb to 1500 then
climbing right turn to
2700 direct ZUBAX
and hold.

ATIS 126.775	PHILADELPHIA APP CON 123.8 291.7	TRENTON TOWER ★ 120.7 (CTAF) 0 257.8	GND CON 121.9 257.8	UNICOM 122.95
------------------------	--	--	-------------------------------	-------------------------



ELEV 213	D	TDZE 213
-----------------	----------	-----------------



MISSED APCH FIX

ZUBAX

058° 238°

4 NM

1500 2700 ZUBAX	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 40).			4 NM Holding Pattern
* LNAV only.	* 1.2 NM to RW16	CULAV 2.5 NM to RW16	HORDE 1900	AMIDY
		* 1060	1900	338° 2700 158°
	1.2 1.3 2.6 NM	6.2 NM		GP 3.00° TCH 55
CATEGORY	A	B	C	D
LPV DA	463-¾ 250 (300-¾)			
LNAV/VNAV DA	529-1 316 (400-1)			
LNAV MDA	640-1	427 (500-1)	640-1¼ 427 (500-1¼)	
CIRCLING	680-1	467 (500-1)	760-1½ 960-2½	547 (600-1½) 747 (800-2½)

NE-2, 01 OCT 2026 to 29 OCT 2026

NE-2, 01 OCT 2026 to 29 OCT 2026