



LOC/DME I-MFE 111.7 Chan 54	APP CRS 137°	Rwy Ldg 6983 TDZE 107 Apt Elev 107
---	------------------------	---

ILS or LOC RWY 14
MC ALLEN INTL (MF'E)

ADF required. Circling NA northeast of Rwy 14-32. When local altimeter setting not received, use Weslaco altimeter setting: increase all DA 39 feet; increase all MDA 40 feet and S-LOC 14 Cat C/D and Circling Cat C visibility 1/8 mile, increase LOBIC Fix Minimums S-LOC 14 Cat C/D visibility 1/4 mile. For inop ALS, increase S-LOC 14 Cat C/D visibility to 1 3/8 SM. For inop ALS when using Weslaco altimeter setting, increase LOBIC Fix Minimums S-LOC 14 Cat C/D visibility to 1 3/8 SM.			MALSR 	MISSED APPROACH: Climb to 1500 then climbing left turn to 2000 direct to MISSI LOM and hold.
ATIS 128.5	VALLEY APP CON 126.55 377.2	MC ALLEN TOWER ★ 118.5 (CTAF) 0 256.9	GND CON 121.8	UNICOM 122.95



Remain within 10 NM		MISSI LOM/I-MFE 6.8		1500		2000		MF	
		1952						*LOC only.	
2000		317°		137°		2000		LOBIC I-MFE 2.7	
GS 3.00° TCH 56						I-MFE 1.3			
*660 when using Weslaco altimeter setting.				*620		4.1 NM		1.4 NM	
CATEGORY	A	B	C	D					
S-ILS 14	307-1/2 200 (200-1/2)								
S-LOC 14	620-1/2	513 (600-1/2)	620-1	513 (600-1)					
CIRCLING	620-1	513 (600-1)	620-1/2 513 (600-1/2)	800-2 1/4 693 (700-2 1/4)					
LOBIC FIX MINIMUMS									
S-LOC 14	540-1/2	433 (500-1/2)	540-3/4	433 (500-3/4)					
CIRCLING	580-1	473 (500-1)	580-1/2 473 (500-1/2)	800-2 1/4 693 (700-2 1/4)					

SC-3, 01 OCT 2026 to 29 OCT 2026

SC-3, 01 OCT 2026 to 29 OCT 2026