



ILS or LOC RWY 11
SAN LUIS OBISPO COUNTY RGNL (SBP)

- | | | | |
|---------------------------------|--|--|--|
| <p>V</p> <p>A</p> | <p>Circling Rwy 25 NA at night. Circling NA north of Rwy 11-29. Autopilot coupled approach NA below 677. For inop ALS, increase S-ILS 11 all Cats visibility to ¾ SM, S-LOC 11 Cat A visibility to 1¼ SM, Cat B visibility to 1½ SM.</p> | <p>MALSR</p>  | <p>MISSED APPROACH: Climb to 1000 then climbing right turn to 3300 on heading 215° and MQO VORTAC R-126 to MQO VORTAC and hold, continue climb-in-hold to 3300. S-ILS 11* missed approach requires minimum climb of 210 feet per NM to 1160.</p> |
|---------------------------------|--|--|--|

ATIS 120.6	SANTA BARBARA APP CON* 127.725 244.575	SAN LUIS TOWER* 124.0 (CTAF) 0 379.9	GND CON 121.6	UNICOM 122.95
---------------	---	---	------------------	------------------



ELEV 212	D	TDZE 198
----------	----------	----------



REIL Rwy 29 **L**
HIRL Rwy 11-29 **L**

FAF to MAP 6.9 NM

Knots	60	90	120	150	180
Min:Sec	6:54	4:36	3:27	2:46	2:18

