


WAAS CH 86538 W29A	APP CRS 289°	Rwy Ldg TDZE Apt Elev	5400 97 97
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 29
ANIAK (ANI)(PANI)

RNP APCH. ⚠ ❄ -37°C	Circling NA north of Rwy 11-29. Rwy 29 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C.	MISSED APPROACH: Climb to 1500 then climbing left turn to 3500 direct APWIS and hold.
---------------------------	--	---

AWOS-3P 124.3	ANCHORAGE CENTER 118.15 251.05	CLNC DEL 118.15	CTAF 122.1
-------------------------	--	---------------------------	----------------------



ELEV 97	D	TDZE 97
----------------	----------	----------------

1500	3500	APWIS	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 40).	
*LNAV only		HAFRU	APWIS	4 NM Holding Pattern
*1.3 NM to RWY 29		1700	109° → 14000	← 289° 3500
1.3 NM		3.6 NM	GP 3.00° TCH 52	
6.2 NM				
CATEGORY	A	B	C	D
LPV DA	347-1 250 (300-1)			
LNAV/ VNAV DA	460-1 363 (400-1)			
LNAV MDA	560-1	463 (500-1)	560-1 3/8	463 (500-1 3/8)
CIRCLING	560-1 463 (500-1)	620-1 523 (600-1)	860-2 1/4 763 (800-2 1/4)	1200-3 1103 (1200-3)