

LOC I-CDB	APP CRS	Rwy Ldg
110.3	146°	10179
		TDZE 75
		Apt Elev 100

ILS or LOC RWY 15

COLD BAY (CDB) (PACD)

DME required.

⚠ Circling NA for Cats B/C/D southwest of Rwy 15-33. DME from CDB VORTAC.


⚠ Simultaneous reception of I-CDB and CDB DME required. DME values will decrease then increase prior to reaching missed approach point. Circling NA for Cat A southwest of Rwy 15-33 at night. For inop ALS, increase S-LOC 15 Cats C and D visibility to RVR 5500. #RVR 1800 authorized with use of FD or AP or HUD to DA.


MALSR



MISSED APPROACH: Climb to 1100 then climbing left turn to 2700 direct CDB VORTAC and hold, continue climb-in-hold to 2700.

ASOS 135.75	ANCHORAGE CENTER 118.5 278.3	COLD BAY RADIO 123.6 (CTAF) 0
-----------------------	--	---



CATEGORY				
	A	B	C	D
	S-ILS 15 # 275/24 200 (200-½)			
	S-LOC 15 440/24 365 (400-½) 440/35 365 (400-½)			
CIRCLING	540-1 440 (500-1)	560-1 460 (500-1)	560-1½ 460 (500-1½)	860-2½ 760 (800-2½)

