

APP CRS
312°

Rwy Ldg
TDZE
43

Apt Elev
46

RNAV (RNP) Z RWY 31

CORPUS CHRISTI INTL (CRP)

▼ For uncompensated Baro-VNAV systems, procedure NA below -1°C (31°F) or above 54°C (130°F). GPS and RF required. For inop MALSR, increase RNP 0.14 all Cats visibility to ¾ mile.
*Missed approach requires minimum climb of 335 feet per NM to 500.

MALSR

MISSED APPROACH: Climb to 2000 on track 312° to ATHIS and hold.

ATIS 126.8	CORPUS APP CON 120.9 348.725	CORPUS TOWER 119.4 257.8	GND CON 121.9 269.15
----------------------	--	------------------------------------	--------------------------------

ELEV 46

D

TDZE 43

7510 X 130

36

312°

2000

ATHIS

See planview for multiple IF locations.

QODLU

646

NIGBE

1200

SIWOC

2400

GP 3.00°

TCH 50

CATEGORY	A	B	C	D
RNP 0.14 DA*		303-1/2	260 (300-1/2)	
RNP 0.30 DA		384-5/8	341 (400-5/8)	

AUTHORIZATION REQUIRED

CORPUS CHRISTI, TEXAS

Amdt 1A 28NOV24

27°46'N-97°30'W

CORPUS CHRISTI INTL (CRP)

RNAV (RNP) Z RWY 31