



WAAS CH 40338 W26A	APP CRS 256°	Rwy Ldg TDZE Apt Elev	4715 8 10
--	------------------------	-----------------------------	--------------------------------------

RNAV (GPS) RWY 26

MICHAEL J SMITH FLD (MRH)

RNP APCH - GPS.	MISSED APPROACH: Climb to 500 then climbing right turn to 3000 direct EWN VOR/DME and hold.
⚠ ⚠ Circling Rwy 8, 14, 32 NA at night. Rwy 26 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C. ATC clearance required to penetrate R-5306A and R-5306C.	

ASOS 135.375	CHERRY POINT APP CON 132.575 299.6	CLNC DEL 125.65	UNICOM 122.8 (CTAF)
------------------------	--	---------------------------	-------------------------------



500	3000	EWN	4 NM Holding Pattern			
						
			MOKEY	CIGOR		
1 NM to RW26			1000	256°	076°	6000
RW26					256°	1900
1 NM			2 NM	6 NM	GP 3.00°	
					TCH 43	
CATEGORY		A		B	C	D
LPV	DA	266-¾		258 (300-¾)		
LNAV/VNAV	DA	394-1⅛		386 (400-1⅛)		
LNAV	MDA	380-1		372 (400-1)		
CIRCLING	540-1	530 (600-1)	580-1½	570 (600-1½)	580-2	570 (600-2)