


WAAS CH 45522 W09A	APP CRS 090°	Rwy Ldg TDZE 707 Apt Elev 712
--	------------------------	---

RNAV (GPS) RWY 9

AURORA MUNI (ARR)

RNP APCH - GPS.		MALSR	MISSED APPROACH: Climb to 2500 direct HOGIE and hold.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to 1 SM, LNAV Cat C/D visibility to 1½ SM.			
ATIS 125.85	CHICAGO APP CON 133.5 349.0	AURORA TOWER ★ 120.6 (CTAF) 0	GND CON 121.7



4 NM Holding Pattern		TOBBY	WOLFF	2500	HOGIE
10000 2700		2700	2700	1.5 NM to RWY 09	RWY 09
GP 3.00° TCH 45		6 NM	4.7 NM	1.5 NM	
CATEGORY	A	B	C	D	
LPV DA	957-½		250 (300-½)		
LNAV/VNAV DA	1086-⅝		379 (400-⅝)		
LNAV MDA	1220-½	513 (600-½)	1220-1	513 (600-1)	
CIRCLING	1220-1	508 (600-1)	1300-1½ 588 (600-1½)	1340-2 628 (700-2)	

MIRL Rwy 18-36 0
HIRL Rwy 15-33 and 9-27 0
REIL Rwy 15, 18, 27, and 36 0