

LOC I-LMJ 110.7	APP CRS 218°	Rwy Ldg 11001 TDZE 964 Apt Elev 964
---------------------------	------------------------	--

ILS or LOC RWY 22

GREENVILLE SPARTANBURG INTL (GSP)

▼



▲

When local altimeter setting not received, use Greenville Downtown altimeter setting: increase DA to 1193; increase all MDAs 40 feet and visibility S-LOC 22 Cats C and D to RVR 3500 and Circling Cat D ¼ SM. For inop ALS, increase S-LOC 22 Cat C/D visibility to RVR 5500.

MALSR

MISSED APPROACH: Climb to 2000 then climbing left turn to 3000 direct SPA VORTAC and hold.

ATIS 134.25	GREER APP CON★ 118.8 270.275	GREER TOWER★ 120.1 (CTAF) 0 251.15	GND CON 121.9	UNICOM 122.95
-----------------------	--	--	-------------------------	-------------------------



2000 3000 SPA				VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 76).	One Minute Holding Pattern
*LOC only.					
				GS 3.00° TCH 61	
CATEGORY	A	B	C	D	
S-ILS 22	1164/24 200 (200-½)				
S-LOC 22	1320/24 356 (400-½)		1320/30 356 (400-¾)		
CIRCLING	1440-1 476 (500-1)		1480-1½ 516 (600-1½)		1700-2¼ 736 (800-2¼)