



WAAS CH 61301 W34A	APP CRS 339°	Rwy Ldg TDZE 329 Apt Elev 346
--	------------------------	---

RNAV (GPS) RWY 34L
JACKSON-MEDGAR WILEY EVERS INTL (JAN)

RNP APCH.				MALS R 	MISSED APPROACH: Climb to 3000 direct MOPKE and hold.
▼ ▲ ASR	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C or above 54°C. Circling NA for Cat E southwest of Rwy 16R-34L. VDP and Baro-VNAV NA when using Hawkins Fld altimeter setting. When local altimeter setting not received, use Hawkins Fld altimeter setting and increase all DA 19 feet and all MDA 20 feet, increase LNAV/VNAV all Cats visibility to 1½ SM and LNAV Cats C/D/E visibility to RVR 5000. For inop ALS, increase LNAV/VNAV Cat E visibility to 1½ SM and LNAV Cat E visibility to 1½ SM. For inop ALS when using Hawkins Fld altimeter setting, increase LPV Cat E visibility to RVR 4500, LNAV/VNAV Cat E visibility to 1½ SM, and LNAV Cat E visibility to 1½ SM. Inop table does not apply to LPV. Rwy 34L helicopter visibility reduction below RVR 4000 NA.				
ATIS 121.05	JACKSON APP CON ★ 123.9 317.7	JACKSON TOWER ★ 120.9 (CTAF) 0 352.0	GND CON 121.7 348.6		UNICOM 122.95



3000 ↑		MOPKE ✧				
* LNAV only.		CEKBI 2 NM to RW34L		DABEY 1800		
RW34L 1.2 NM		*1.2 NM to RW34L 0.8 NM		*1020 2.4 NM		
				7.2 NM		
				FAVIN		
				7 NM Holding Pattern		
				159° → ← 339° 3000		
				GP 3.00° TCH 58		
CATEGORY	A		B	C	D	E
LPV DA			579/40 250 (300-¾)			
LNAV/ VNAV DA			875-1⅜ 546 (600-1⅜)			
LNAV MDA	780/40 451 (500-¾)		780/45 451 (500-¾)			
CIRCLING	880-1 534 (600-1)	900-1 554 (600-1)	900-1½ 554 (600-1½)	960-2 614 (700-2)	1040-2½ 694 (700-2½)	