

LOC I-AOH 109.3	APP CRS 276°	Rwy Idg TDZE Apt Elev	6000 975 975
---------------------------	------------------------	-----------------------------	---


ILS or LOC RWY 28
LIMA ALLEN COUNTY (AOH)

⚠ NA

When local altimeter setting not received, use Findlay altimeter setting and increase S-ILS DA to 1255 and all MDA's 80 feet; increase S-ILS all Cats visibility $\frac{1}{8}$ SM, S-LOC Cats C/D and Circling Cats C/D visibility $\frac{1}{4}$ SM.

MISSED APPROACH: Climb to 3000 on heading 276° and right turn on ROD VORTAC R-360 to LINZZ INT/ROD 31.2 DME and hold.

ASOS 128.725	COLUMBUS APP CON 121.825 323.15	UNICOM 122.7 (CTAF) 0
------------------------	---	---------------------------------



ELEV 975 TDZE 975

REIL Rwy 10 and 28 1
HIRL Rwy 10-28 1

FAF to MAP 3.7 NM

Knots	60	90	120	150	180
Min:Sec	3:42	2:28	1:51	1:29	1:14

3000
hdg 276°
ROD R-360
LINZZ INT

WEVIG INT
2200
2700
276°
2200
GS 3.00°
TCH 49

Remain within 10 NM

3.7 NM

CATEGORY	A	B	C	D
S-ILS 28	1175- $\frac{3}{4}$ 200 (200- $\frac{3}{4}$)			
S-LOC 28	1500-1 525 (600-1)		1500-1 $\frac{1}{2}$ 525 (600-1 $\frac{1}{2}$)	
CIRCLING	1500-1 525 (600-1)		1540-1 $\frac{1}{2}$ 565 (600-1 $\frac{1}{2}$) 1820-2 $\frac{3}{4}$ 845 (900-2 $\frac{3}{4}$)	