

WAAS CH 90108 W17A	APP CRS 174°	Rwy Ldg 7401 TDZE 1000 Apt Elev 1000	RNAV (GPS) RWY 17 STILLWATER RGNL (SWO)
--	------------------------	---	---

RNP APCH - GPS.		MALSR 	MISSED APPROACH: Climb to 3000 direct ESCOM and hold.
▼ ▲	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. VDP and Baro-VNAV NA when using Ponca City altimeter setting. For inop ALS when using Ponca City altimeter setting, increase LPV visibility to ¾ SM, LNAV/VNAV visibility to 1 SM, and LNAV Cats C and D visibility to 1¾ SM. When local altimeter setting not received, use Ponca City altimeter setting: increase LPV DA to 1280 feet; increase LNAV/VNAV DA to 1359 feet and all visibilities ¾ SM; increase all MDA 80 feet and visibility LNAV Cats C and D ¼ SM and Circling Cat D ½ SM. For inop ALS, increase LNAV/VNAV visibility to ¾ SM.		

ASOS 135,725	KANSAS CITY CENTER 127.8 319.1	STILLWATER TOWER ★ 125.35 (CTAF) 0	GND CON 121.6	UNICOM 122,95
------------------------	--	--	-------------------------	-------------------------

