

LOC/DME	I-ALN	APP CRS	Rwy Ldg	8099
108.5		294°	TDZE	531
Chan 22			Apt Elev	544

ILS or LOC RWY 29

ST LOUIS RGNL (ALN)

⚠


For inop ALS, increase WULIB fix minimums S-LOC 29 Cats C/D visibility to 1 SM.

MALSR

MISSED APPROACH:

Climb to 1000 then climbing right turn to 2200 on heading 310° and on TOY VORTAC R-322 to TOPAZ INT/TOY 16 DME and hold.

ATIS 128.0	ST LOUIS APP CON 124.2 353.9	REGIONAL TOWER★ 126.0 (CTAF) 239.0	GND CON 120.2	UNICOM 122.95
---------------	---------------------------------	---------------------------------------	------------------	------------------



ELEV 544	D	TDZE 531	Procedure NA for arrivals at JACOB on V12 northeast bound.			
		1000	2200	TOY R-322	TOPAZ INT	*LOC only.
		hdg 310°				
				OSERE INT I-ALN 6.2	QUNIE INT I-ALN 13	JACOB I-ALN 19
				WULIB INT I-ALN 2.9	2100	2100
				I-ALN 1.5	2100	2100
				1.4 NM	3.3 NM	6.8 NM
				A	B	C
				S-ILS 29	731-1/2	200 (200-1/2)
				S-LOC 29	980-1/2	449 (500-1/2)
				CIRCLING	1000-1	456 (500-1)
					1160-13/4	1200-2
					616 (700-13/4)	656 (700-2)
					WULIB FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)	
				S-LOC 29	880-1/2	349 (400-1/2)
				CIRCLING	1000-1	456 (500-1)
					1160-13/4	1200-2
					616 (700-13/4)	656 (700-2)