



WAAS CH 78300 W27A	APP CRS 269°	Rwy Ldg 5000 TDZE 910 Apt Elev 912
--	------------------------	---

RNAV (GPS) RWY 27

ANOKA COUNTY/BLAINE (JANES FLD) (A.NE)

RNP APCH - GPS. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Crystal altimeter setting: increase LPV DA to 1131 feet; increase LNAV/VNAV DA to 1361 feet and all visibilities ½ SM, increase all MDA 40 feet and visibility Cat C/D ¼ SM, and Circling visibility Cat D ¼ SM. Baro-VNAV and VDP NA when using Crystal altimeter setting. For inop ALS when using Crystal altimeter setting, increase LNAV Cat C/D visibility to 1 ½ SM.		MALSR 	MISSED APPROACH: Climb to 2700 direct GEP VORTAC and hold, continue climb-in-hold to 2700.	
ATIS 120.625	MINNEAPOLIS APP CON 126.5 335.65	ANOKA TOWER★ 132.4 (CTAF) 0	GND CON 121.85	UNICOM 122.95



2700 ↑ GEP ⬡		KOGGE 2.6 NM to RW27 BOKYA 2600 JUDAL 4 NM Holding Pattern 089° → 6000 ← 269° 3100 GP 3.00° TCH 49 1.2 NM 1.4 NM 2.6 NM 10.5 NM			
CATEGORY		A	B	C	D
LPV DA		1110-½ 200 (200-½)			
LNAV/VNAV DA		1340-¾ 430 (500-¾)			
LNAV MDA		1340-½ 430 (500-½)		1340-¾ 430 (500-¾)	
CIRCLING		1400-1 488 (500-1)		1420-1½ 508 (600-1½)	1580-2 668 (700-2)

NC-1, 01 OCT 2026 to 29 OCT 2026

NC-1, 01 OCT 2026 to 29 OCT 2026