

ATIS  
128.375  
CLNC DEL  
119.45  
GND CON  
121.8 239.0  
HOOKS TOWER ★  
127.4 354.1 (EAST)  
118.4 (CTAF) 354.1 (WEST)  
HOUSTON DEP CON  
119.7 281.4

TOP ALTITUDE:  
ASSIGNED BY ATC

NOTE: RADAR required.  
NOTE: DME/DME/IRU or GPS required.  
NOTE: RNAV 1.

TAKEOFF MINIMUMS

Rwys 17L, 35R: NA - Environmental.  
Waterways 17, 35: NA - Air Traffic.  
Rwys 17R, 35L: Standard with minimum  
climb of 500' per NM to 660.


▼ DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 17R: Climb on heading  
168° to 660 for RADAR vectors to  
DREMR, thence. . .

TAKEOFF RUNWAY 35L: Climb on heading  
348° to 660 for RADAR vectors to  
DREMR, thence. . .

. . . on track 345° to LITLD, then on track  
346° to BLTWY, then on (transition).  
Maintain ATC assigned altitude. Expect  
filed altitude 10 minutes after departure.

CRIED TRANSITION (BLTWY7.CRIED)



NOTE: Chart not to scale.