

APP CRS
087°

Rwy Ldg **10000**
TDZE **91**
Apt Elev **96**

RNAV (RNP) Y RWY 9

GEORGE BUSH INTCNL/HOUSTON (IAH)

▼

For uncompensated Baro-VNAV systems, procedure NA below -3°C (27°F) or above 54°C (130°F). GPS required. For inop MALSR, increase all Cats visibility to 1½ mile. Simultaneous approach authorized. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

MISSED APPROACH: Climb to 580 then climbing right turn to 3000 direct JEBOX and hold.

D-ATIS 124.05	HOUSTON APP CON 120.05 379.1 E 124.35 316.15 W	HOUSTON TOWER 135.15 290.2	GND CON 118.575
-------------------------	--	--------------------------------------	---------------------------

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).

580

3000

JEBOX

SAYNO

HYWAY

3000

2000

2000

087°

GP 3.00° TCH 50

4.7 NM

5.8 NM

RWY 09

CATEGORY	A	B	C	D
RNP 0.30 DA	516/49 425 (500-1)			

AUTHORIZATION REQUIRED

ELEV 96

TDZE 91

TDZ/CL Rwy 8R, 8L, 15R, 26R, 26L, 27 and 33L

HIRL all Rwy

HOUSTON, TEXAS

Orig-B 13SEP18

GEORGE BUSH INTCNL/HOUSTON (IAH)

29°59'N-95°20'W

RNAV (RNP) Y RWY 9