




WAAS CH 69626 W27A	APP CRS 267°	Rwy Ldg 10000 TDZE 86 Apt Elev 96
--	------------------------	--

RNAV (GPS) Z RWY 27
GEORGE BUSH INTCNL/HOUSTON (IAH)

RNP APCH. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -2°C or above 54°C. For inop ALS, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV Cat E visibility to RVR 6000, and LNAV Cats C, D and E visibility to 1½ SM.	ALSF-2 	MISSED APPROACH: Climb to 560 then climbing left turn to 3100 direct TICOF and hold.
--	------------	--

D-ATIS 124.05	HOUSTON APP CON 120.05 379.1 E 124.35 316.15 W	HOUSTON TOWER 135.15 290.2	GND CON 118.575
-------------------------	--	--------------------------------------	---------------------------



560	3100	TICOY	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 70).		
					
*LNAV only.					
					
CATEGORY	A	B	C	D	E
LPV DA	286/18 200 (200-½)				
LNAV/VNAV DA	476/35 390 (400-⅝)				
LNAV MDA	560/24	474 (500-½)	560/50	474 (500-1)	

SC-5, 01 OCT 2026 to 29 OCT 2026

SC-5, 01 OCT 2026 to 29 OCT 2026