


WAAS CH 53626 W08B	APP CRS 087°	Rwy Ldg TDZE 96 Apt Elev 96
--	------------------------	---


RNAV (GPS) Z RWY 8R

GEORGE BUSH INTCNL/HOUSTON (IAH)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -3°C (27°F) or above 54°C (130°F). For inop MALSR, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV all Cats visibility to RVR 6000, and LNAV Cat C/D/E visibility to 1½. Simultaneous approach authorized with Rwy 8L and Rwy 9. DME/DME RNP-0.3 NA. Use of FD or AP providing RNAV track guidance required during simultaneous operations. LNAV procedure NA during simultaneous operations.		MALSR 	MISSED APPROACH: Climb to 3000 direct MKAYE and hold.
D-ATIS 124.05	HOUSTON APP CON 120.05 379.1 E 124.35 316.15 W	HOUSTON TOWER 125.35 290.2	GND CON 118.575



ELEV 96		D TDZE 96	
DPLOY		3000 MKAYE	
7000 087°		*INAV only.	
5000		*1.3 NM to RWY 08R	
REIGN		RWY 08R	
EELPO		2000	
MATON		2000	
GP 3.00° TCH 55		33R	
4.2 NM		3.8 NM	
3.9 NM		3.6 NM	
4.5 NM		1.3 NM	
CATEGORY	A	B	C
LPV DA	296/18	200 (200-½)	
LNAV/VNAV DA	421/32	325 (400-¾)	
LNAV MDA	580/24	484 (500-½)	580/50 484 (500-1)



HIRL all Rwy's
TDZ/CL Rwy's 8L/R, 15R, 26L/26R, 27 and 33L