

WAAS CH 62824 W28A	APP CRS 282°	Rwy Ldg TDZE 969 Apt Elev 974	5041 969 974
--	------------------------	---	---

RNAV (GPS) RWY 28

POLK COUNTY/CORNELIUS MOORE FLD (4A4)

RNP APCH.


▼

▲ NA


Baro-VNAV and VDP NA when using Cartersville altimeter setting. Rwy 28 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C or above 54°C. Obtain local altimeter setting on CTAF, when not received, use Cartersville altimeter setting; increase LPV DA to 1287 feet; increase LNAV/VNAV DA to 1353 feet and all visibility $\frac{1}{2}$ SM; increase all MDAs 80 feet and visibility Cats C and D $\frac{1}{2}$ SM.

MISSED APPROACH:
Climb to 1500 then climbing left turn to 3100 direct GUSSY and hold.

ATLANTA CENTER 124.5 270.325	UNICOM 122.8 (CTAF) 0
--	---------------------------------



ELEV 974	TDZE 969
----------	----------



1500	3100	GUSSY							
↑	↶	✧	ZIRIX 2.4 NM to RW28	ANTOW 2600	GUSSY	4 NM Holding Pattern			
*LNAV only.			*1 NM to RW28	1740*	2600	282°	102°	6000	3100
			1 NM	1.4 NM	2.7 NM	6.6 NM			
CATEGORY		A	B	C	D				
LPV DA		1219-1 250 (300-1)							
LNAV/VNAV DA		1285-1 316 (400-1)							
LNAV MDA		1300-1 331 (400-1)							