




CHARLOTTE DEP CON 128.325 307.8 AWOS-3P 118.175 CLNC DEL 127.35	RNAV 1 - DME/DME/IRU or GPS. RADAR required.	TOP ALTITUDE: 3000
--	---	-----------------------

TAKEOFF MINIMUMS

Rwy 2: Standard.
Rwy 20: 400-2¾ or standard with minimum climb of 203’/NM to 1300, or alternatively, with standard takeoff minimums and a normal 200’/NM climb gradient, takeoff must occur no later than 1300’ prior to DER.



- NOTE: Turbojet only.
NOTE: If unable to accept climb rates, advise ATC on initial contact.
NOTE: Transponder code will be issued via PDC or CLT CLNC DEL.
NOTE: Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC.



NOTE: Chart not to scale.

▼ DEPARTURE ROUTE DESCRIPTION TAKEOFF RUNWAY 2: Climb on assigned heading for vectors to GINNN, thence. . . TAKEOFF RUNWAY 20: Climb on heading 202° to 1700 before turning right for vectors to GINNN, thence. on track 255° to ESTRR, then on IPTAY Transition. Maintain 3000, expect filed altitude 10 minutes after departure. <u>IPTAY TRANSITION (ESTRR8.IPTAY)</u>

SE-2, 01 OCT 2026 to 29 OCT 2026

SE-2, 01 OCT 2026 to 29 OCT 2026