


CHARLOTTE DEP CON
128.325 307.8
AWOS-3P
118.175
CLNC DEL
127.35

TOP ALTITUDE:
3000


RNAV 1 - DME/DME/IRU or GPS.
RADAR required.

TAKEOFF MINIMUMS

Rwy 2: Standard.
Rwy 20: 400-2¾ or standard with minimum climb of 203'/NM to 1300, or alternatively, with standard takeoff minimums and a normal 200'/NM climb gradient, takeoff must occur no later than 1300' prior to DER.



- NOTE: Jet aircraft only.
- NOTE: Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC.



NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 2: Climb on assigned heading for vectors to JDEAN, thence. . .
TAKEOFF RUNWAY 20: Climb on heading 202° to 1700 before turning right for vectors to JDEAN, thence. . .

. . . on depicted route to KRITR, then on assigned transition. Maintain 3000.
Expect filed altitude 10 minutes after departure.

FILDS TRANSITION (KRITR9.FILDS)
SMIAM TRANSITION (KRITR9.SMIAM)

SE-2, 01 OCT 2026 to 29 OCT 2026

SE-2, 01 OCT 2026 to 29 OCT 2026