

LOC/DME I-FGH 109.35 Chan 30 (Y)	APP CRS 041°	Rwy Ldg 4775 TDZE 58 Apt Elev 72
--	------------------------	---

ILS or LOC RWY 4

EASTON/NEWNAM FLD (ESN)

RADAR and DME required for procedure entry. DME required for LOC only.


▼

▲

Circling Rwy 15, 33 NA at night. Autopilot coupled approach NA below 1000.

MISSED APPROACH: Climb to 2000 on heading 041° and on ATR VOR/DME R-283 to ORETE INT/ATR 31.6 DME and hold.

ATIS 124.475	POTOMAC APP CON 133.75 254.35	EASTON TOWER ★ 118.525 (CTAF) 0	GND CON 119.075
------------------------	---	---	---------------------------



One Minute Holding Pattern		GS unusable below 600.	2000	ATR R-283	ORETE
RIKME I-FGH 11.8		WEGRO I-FGH 5.8	hdg 041°		△
4600	← 221°	041° →	1600	* I-FGH 2.5	I-FGH 1
2000					
GS 3.00° TCH 44		6 NM	3.4 NM	1.4 NM	
CATEGORY	A	B	C	D	
S-ILS 4		600-1 ⁵ / ₈	542 (600-1 ⁵ / ₈)		
S-LOC 4	540-1	482 (500-1)	540-1 ³ / ₈	482 (500-1 ³ / ₈)	
CIRCLING	540-1 468 (500-1)	640-1 568 (600-1)	640-1 ¹ / ₂ 568 (600-1 ¹ / ₂)	740-2 ¹ / ₄ 668 (700-2 ¹ / ₄)	

