WAAS	APP CRS	Rwy Ldg	6002
CH 69609	249°	TDZE	273
W25A		Apt Elev	274

AL-5607 (FAA)

RNAV (GPS) RWY 25

VIDALIA RGNL (VDI)


RNP APCH - GPS.

Circling Rwy 32 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to ⅞ SM and LNAV Cat C/D to 1⅜ SM.


MALSR


MISSED APPROACH: Climb to 2000 direct FEVKO and hold.

AWOS-3	JACKSONVILLE CENTER	UNICOM
119.925	127.575 269.025	122.8 (CTAF) L



ELEV 274 | TDZE 273





CATEGORY	A	B	C	D
LPV DA	473-½ 200 (200-½)			
LNAV/VNAV DA	584-½ 311 (400-½)			
LNAV MDA	740-½ 467 (500-½)		740-1 467 (500-1)	
CIRCLING	740-1 466 (500-1)		920-1¾ 646 (700-1¾)	1060-2½ 786 (800-2½)

HIRL Rwy 7-25 L
REIL Rwy 7 L

SE-4, 01 OCT 2026 to 29 OCT 2026