

WAAS CH 90528 W24A	APP CRS 242°	Rwy Ldg TDZE Apt Elev	4000 785 786
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 24


SENECA COUNTY(16G)

RNP APCH. ▼ ▲ NA Circling to Rwy 24 NA at night. Baro-VNAV NA when using Findlay altimeter setting. Rwy 24 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Findlay altimeter setting and increase all DA/MDA 60 feet, and increase LPV, LNAV/VNAV all Cats visibility $\frac{1}{8}$ SM, increase LNAV and Circling Cat C visibility $\frac{1}{4}$ mile.	MISSED APPROACH: Climb to 2400 direct MAZKY and hold.
---	--

AWOS-3PT 127.175	FDY ASOS 132.85	TOLEDO APP CON 120.8 317.55	UNICOM 123.0 (CTAF) 0
----------------------------	---------------------------	---------------------------------------	---------------------------------

MISSED APCH FIX

MAZKY



ELEV 786

TDZE 785

MIRL Rwy 6-24 0
REIL Rws 6 and 24 0

2400 ↑		MAZKY 		TIPEJ 2400 		VOBRY 		4 NM Holding Pattern	
		RW24		2400 ←242°		←242°		062°→ 2400	
4.9 NM		6.5 NM						GP 3.00° TCH 38	
CATEGORY	A		B		C		D		
LPV DA	1058-1		273 (300-1)				NA		
LNAV/VNAV DA	1063-1		278 (300-1)				NA		
LNAV MDA	1280-1	495 (500-1)		1280-1 ³ / ₈ 495 (500-1 ³ / ₈)				NA	
CIRCLING	1280-1	494 (500-1)		1340-1 ¹ / ₂ 554 (600-1 ¹ / ₂)				NA	