

WAAS

CH **93528**

W36A

APP CRS

003°

Rwy Ldg

5001

TDZE

343

Apt Elev

343

RNAV (GPS) RWY 36

NACOGDOCHES A L MANGHAM JR RGNL (OCH)

RNP APCH-GPS.

▼

Baro-VNAV NA when using LFK altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use LFK altimeter setting: Increase LPV DA to 598 feet; increase LNAV/VNAV DA to 680 feet; increase all MDAs 60 feet and LNAV visibility Cat C ¼ SM, and Circling visibility Cat C ¼ SM.

MALSR

MISSED APPROACH: Climb to 2400 direct XOWNU and on track 356° to DRBOB and hold.

AWOS-3PT 135.625	HOUSTON CENTER 125.175 285.575	UNICOM 123.0 (CTAF) 0
----------------------------	--	---------------------------------

MISSED APCH FIX

4 NM Holding Pattern		ZIVIM	2400 XOWNU	DRBOB
		ZARAD	↑	fr 356°
GP 3.00° TCH 53		2100	YIRUN 1.5 NM to RW36	RW36
		840		
		7.3 NM	3.9 NM	1.5 NM
CATEGORY	A	B	C	D
LPV DA	543-½ 200 (200-½)		NA	
LNAV/VNAV DA	625-½ 282 (300-½)		NA	
LNAV MDA	720-½	377 (400-½)	720-5/8 377 (400-5/8)	NA
CIRCLING	860-1	517 (600-1)	1080-2 737 (800-2)	NA

ELEV 343

TDZE 343

NACOGDOCHES, TEXAS

Orig-E 22JAN26

NACOGDOCHES A L MANGHAM JR RGNL (OCH)

31°35'N-94°43'W

RNAV (GPS) RWY 36