

WAAS CH 56604 W18A	APP CRS 188°	Rwy Ldg TDZE 226 Apt Elev 226
--	------------------------	---

RNAV (GPS) RWY 18


MONROE COUNTY (M40)

RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

MISSED APPROACH: Climb to 800 then climbing left turn to 2000 direct VEPPU and hold.

AWOS-3P 118.475	COLUMBUS APP CON ★ 126.075 239.25	UNICOM 122.8 (CTAF) 0
---------------------------	---	---------------------------------



ELEV 226	TDZE 226
----------	----------

188°

81

4999 X 75

36

REIL Rwsys 18 and 36 0
MIRL Rwy 18-36 0

800	2000	VEPPU	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 40).			
*LNAV only.		YOYVO 2 NM to RW18	PIYIG 1900	VEPPU	4 NM Holding Pattern	
*1.1 NM to RW18		*900	1900	2000	GP 3.00° TCH 40	
1.1 NM		0.9	3.1 NM	6 NM		
CATEGORY	A	B	C	D		
LPV DA	476-3/4		250 (300-3/4)			
LNAV/VNAV DA	504-7/8		278 (300-7/8)			
LNAV MDA	600-1		374 (400-1)			
CIRCLING	660-1 434 (500-1)	680-1 454 (500-1)	820-1½ 594 (600-1½)	860-2 634 (700-2)		