

APP CRS
097°

Rwy Ldg
TDZE
Apt Elev

5049
1113
1136

RNAV (GPS) RWY 10

WAYNE COUNTY (BJJ)

⚠

⚠

DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Akron-Canton Rgnl altimeter setting and increase all MDA 60 feet and visibility Circling Cat C/D ¼ SM.

MISSED APPROACH:
Climb to 3000 direct DEHYY and hold.

ASOS 118.075	CLEVELAND APP CON ★ 125.5 371.875	CLNC DEL 121.75	UNICOM 122.975 (CTAF) ①
-----------------	--------------------------------------	--------------------	----------------------------

The main chart displays the RNAV (GPS) RWY 10 approach. Key features include:

- Initial Descent:** From 3000 ft, a 30 NM arc leads to the (IAF) PONOC. A 20 NM arc then leads to the (IF/IAF) JAVNE. A 6 NM holding pattern is established at JAVNE.
- Final Approach:** From JAVNE, a 3000 NoPT descent leads to the (FAF) TONSR. A 2800 ft altitude is maintained for 6 NM. The final approach is a 2.2 NM segment to RW10, with a 1289± ft altitude.
- Obstacles:** Obstacles are shown at 1481 ft (near TONSR) and 1289± ft (near RW10).
- Other Points:** The (IAF) FESEK is shown with a 3000 ft altitude. A 30 NM arc leads from FESEK to the 2800 ft altitude. A 6 NM holding pattern is also shown at DEHYY.

6 NM Holding Pattern

VGSI and descent angles not coincident (VGSI Angle 3.04/TCH 33).

3000 DEHYY

JAVNE

TONSR

COPAK 2.2 NM to RW10

2800

1860

3.04° TCH 40

097°

277°

6 NM

2.9 NM

2.2 NM

CATEGORY	A	B	C	D
LNAV MDA	1540-1	427 (500-1)	1540-1¼ 427 (500-1¼)	1540-1½ 427 (500-1½)
CIRCLING	1600-1 464 (500-1)	1700-1 564 (600-1)	1800-1¾ 664 (700-1¾)	1840-2¼ 704 (800-2¼)

REIL Rwy 10 and 28 ①

HIRL Rwy 10-28 ①

WOOSTER, OHIO

Orig-A 12AUG21

40°52'N-81°53'W

WAYNE COUNTY (BJJ)

RNAV (GPS) RWY 10