

LOC I-LQG 111.7	APP CRS 073°	Rwy Ldg TDZE Apt Elev	5002 793 793
---------------------------	------------------------	-----------------------------	---

ILS or LOC RWY 7

LORAIN COUNTY RGNL (LPR)


For inoperative MALSR, increase S-LOC 7 Cats C/D visibility to 1¾ mile. VDP NA with Cleveland-Hopkins Intl altimeter setting. When local altimeter setting not received, use Cleveland-Hopkins Intl altimeter setting and increase all DA 36 feet and all MDA 40 feet.

MALSR

MISSED APPROACH:

Climb to 1400 then climbing left turn to 3000 on heading 270° then left turn direct DJB VOR/DME and hold.

ASOS 118.925	CLEVELAND APP CON 125.35 346.325	CLNC DEL 125.7	UNICOM 122.7 (CTAF) 0
------------------------	--	--------------------------	---------------------------------



Remain within 10 NM

RAWLS OM DJB 5.8

2500 073° 2263 2500

GS 3.00° TCH 54

1400 3000 hdg 270° DJB

* DJB 2.8

* LOC only.

3 NM 1.4 NM

CATEGORY	A	B	C	D
S-ILS 07	993-½ 200 (200-½)			
S-LOC 07	1280-½ 487 (500-½)		1280-1 487 (500-1)	
CIRCLING	1280-1 487 (500-1)	1360-1 567 (600-1)	1420-1¾ 627 (700-1¾)	1420-2 627 (700-2)

REIL Rwy 25 0

HIRL Rwy 7-25 0

5002 X 100

073°

FAF to MAP 4.4 NM	
Knots	60 90 120 150 180
Min:Sec	4:24 2:56 2:12 1:46 1:28

EC-2, 01 OCT 2026 to 29 OCT 2026

EC-2, 01 OCT 2026 to 29 OCT 2026