

WAAS

CH 56611

W23A

APP CRS

233°

Rwy Ldg

4699

TDZE

431

Apt Elev

434

RNAV (GPS) RWY 23

SARATOGA COUNTY (5B2)

RNP APCH.


▼

NA

Baro-VNAV and VDP NA when using Albany altimeter setting. Rwy 23 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Circling NA at night. When local altimeter setting not received, use Albany altimeter setting and increase all DAs 63 feet and MDAs 80 feet. Increase LPV and LNAV/VNAV all Cats visibility ½ SM, LNAV Cats C/D visibility ¾ SM, and Circling Cat C visibility ¼ SM.

MISSED APPROACH: Climb to 3000 direct WALTU and hold.

AWOS-3 132.025	ALBANY APP CON 118.05 263.075	GCO 118.125	UNICOM 123.075 (CTAF) 0
-------------------	----------------------------------	----------------	----------------------------



ELEV 434

TDZE 431

3000

WALTU

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 43).

WEVOP

2.1 NM to RW23

LOXFO

2300

TAYVO

4 NM Holding Pattern

*LNAV only

RW23

1 NM

1.1

3.6 NM

6 NM

1140

2300

GP 3.00°

TCH 55

CATEGORY	A	B	C	D
LPV DA		698-7/8	267 (300-7/8)	
LNAV/VNAV DA		706-7/8	275 (300-7/8)	
LNAV MDA		800-1	369 (400-1)	
CIRCLING	980-1 546 (600-1)	1080-1 646 (700-1)	1140-2 706 (800-2)	1340-3 906 (1000-3)