

WAAS CH 56306 W22A	APP CRS 218°	Rwy Ldg TDZE Apt Elev	5000 315 316
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 22

CULPEPER RGNL (CJR)

RNP APCH - GPS.

▼


▲

Rwy 22 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 48°C. Baro-VNAV and VDP NA when using IAD altimeter setting. When local altimeter setting not received, use IAD altimeter setting and increase LPV DA to 730 feet; increase LNAV/VNAV DA to 776 feet; increase all MDAs 80 feet and visibility Cats C ¼ SM and D ½ SM.

MISSED APPROACH:

Climb to 3000 direct FAXIK and hold.

AWOS-3PT 119.325	POTOMAC APP CON 128.525 306.925	CLNC DEL 121.6	UNICOM 123.075 (CTAF) 0
----------------------------	---	--------------------------	-----------------------------------



ELEV 316

TDZE 315

218°

22

5000 X 100

MIRL Rwy 4-22

REIL Rws 4 and 22

3000

FAXIK

DOYAT

4 NM Holding Pattern

CALPE

1.4 NM to RW22

2200

GP 3.00° TCH 40

1.4 NM 4.3 NM 6.1 NM

CATEGORY	A	B	C	D
LPV DA	657-1¼ 342 (400-1¼)			
LNAV/VNAV DA	703-1½ 388 (400-1½)			
LNAV MDA	800-1	485 (500-1)	800-1¼ 485 (500-1¼)	800-1½ 485 (500-1½)

NE-3, 01 OCT 2026 to 29 OCT 2026

NE-3, 01 OCT 2026 to 29 OCT 2026