




APP CRS	Rwy Ldg	5000
179°	TDZE	1316
	Apt Elev	1321

RNAV (GPS) RWY 18
FLOYD W JONES LEBANON (LBO)

RNP APCH - GPS.	
Baro-VNAV and VDP NA when using OZS altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Rwy 18 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use OZS altimeter setting: increase LNAV/VNAV DA to 1717 feet and all visibilities ½ SM; increase all MDAs 100 feet and LNAV visibility Cats C and D ¼ SM, and Circling visibility Cats C and D ½ SM.	MISSED APPROACH: Climb to 3500 direct PYLER and hold.

AWOS-3PT 118.975	SPRINGFIELD APP CON 121.1 290.5	CLNC DEL 123.725	UNICOM 122.8 (CTAF) 0
---------------------	------------------------------------	---------------------	--------------------------



3500

↑

PYLER



WIKGI

4 NM

Holding Pattern

1.2 NM to RW18

1.2 NM

3 NM

5.8 NM

AAMBR

2700

179°

2700

359° → 6000

← 179° 3500

GP 3.00°

TCH 40

CATEGORY	A	B	C	D
LNAV/VNAV DA	1634-1 318 (400-1)			
LNAV MDA	1740-1	424 (500-1)	1740-1¼	424 (500-1¼)
CIRCLING	1780-1 459 (500-1)	1860-1 539 (600-1)	1980-1¾ 659 (700-1¾)	1980-2 659 (700-2)

NC-3, 01 OCT 2026 to 29 OCT 2026

NC-3, 01 OCT 2026 to 29 OCT 2026