


WAAS CH 72742 W13A	APP CRS 135°	Rwy Ldg 9300 TDZE 591 Apt Elev 606
--	------------------------	---

RNAV (GPS) Y RWY 13R

DALLAS-FORT WORTH INTL (DFW)

RNP APCH - GPS. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8° C or above 54° C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000 and LNAV Cat C/D visibility to 1½ SM.	MALSR 	MISSED APPROACH: Climb to 1100 then climbing right turn to 3000 direct SLOTT and hold.
---	-----------	--

D-ATIS 123.775	LONE STAR APP CON 133.15 118.1	DFW TOWER 126.55 127.5 (E) 124.15 134.9 (W)	GND CON 121.65 121.8 (E) 121.85 (W)
--------------------------	--	---	---



VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 71).		1100	3000	SLOTT
GP 3.00° TCH 55				
CATEGORY	A	B	C	D
LPV DA		791/18	200 (200-½)	
LNAV/VNAV DA		991/35	400 (400-¾)	
LNAV MDA	1080/24	489 (500-½)	1080/50	489 (500-1)

HIRL all Rwys
REIL Rwy's 13L and 31L
TDZL/RCLS all Rwy's except 13L and 31L