

APP CRS
188°

Rwy Ldg
TDZE
Apt Elev

3501
1204
1207

RNAV (GPS) RWY 19
ASHLAND COUNTY (3G4)

RNP APCH.

▼

▲ NA

Rwy 19 helicopter visibility reduction below 1 SM NA.
Procedure NA at night. Use Mansfield altimeter setting,
when not received use Wooster altimeter setting.

MFD ASOS
125.3

CLEVELAND APP CON ★
128.35 360.65

UNICOM
122.7 (CTAF) 1

4 NM
008°
3000 NoPT (5)
(IAF) CIDUX
(IF/IAF) ECZIF
3000 NoPT (5)
(IAF) FEPEV
2800
188° (6.1)
(FAF) JUKAP
RWY 19 1299±
HINPO 098° (5.3)
READS 285°
4 NM
30 NM to ECZIF (NoPT) 3100
1.5 NM to ECZIF 3000
098° ECZIF 278°
098° CIDUX 3000 30 NM to CIDUX 080°
278° FEPEV 3100 30 NM to FEPEV 080°

ELEV 1207

TDZE 1204

188°

61

0.5% UP

3501 X 7.5

1

3000

HINPO

tr 098°

READS

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 20).

4 NM Holding Pattern

JUKAP

3.04° TCH 40

188°

2800

008°

188°

3000

4.9 NM

6.1 NM

CATEGORY	A	B	C	D
LNAV MDA	1600-1	396 (400-1)	1600-1 ¹ / ₈ 396 (400-1 ¹ / ₈)	NA
CIRCLING	1660-1	453 (500-1)	1740-1 ¹ / ₂ 533 (600-1 ¹ / ₂)	NA

ASHLAND, OHIO
Orig-F 09SEP21

40°54'N-82°15'W

ASHLAND COUNTY (3G4)
RNAV (GPS) RWY 19