

LOC/DME I-CFQ
110.35
Chan **40** (Y)

APP CRS
101°

Rwy Ldg **4001**
TDZE **928**
Apt Elev **928**

LOC/DME RWY 10

MIDDLETON MUNI/MOREY FLD (C29)

Helicopter visibility reduction below ¾ SM NA. Use Dane County Rgnl-Truax Fld altimeter setting; when not received, use Baraboo altimeter setting and increase all MDAs 60 feet and S-10 Cat C visibility ¼ SM and Circling Cat C visibility ¼ SM. Circling NA to Rwys 1 and 19.

MISSED APPROACH: Climb to 1700 then climbing left turn to 3600 via heading 010° and MSN VORTAC R-282 to IMMES Int/MSN 9.2 DME and hold, continue climb-in-hold to 3600.

AWOS-3 118.675	MADISON APP CON★ 135.45 343.7	UNICOM 123.0 (CTAF) 0
--------------------------	---	--

The main enroute chart displays the following information:

- Navigation Aids:** IMMES MSN 9.2, MADISON 108.6 MSN Chan 23, LOCALIZER 110.35 I-CFQ Chan 40(Y).
- Altitudes:** 1700, 2900, 264° (14.4), 1240, 101°.
- Angles:** 102°, 282°, 281°, 101°.
- Distances:** 117.0 DME, 117, 101° 1 min, 101°.
- Obstacles:** Obstacle at 1050 x 120.
- Other:** (IAF) CERTO I-CFQ 6.5, R-153, R-282.

MSA MSN 25 NM diagram showing altitudes and angles:

- Altitudes: 3600, 3100.
- Angles: 177°, 357°.

One Minute Holding Pattern

CERTO I-CFQ 6.5

1700

3600

IMMES MSN 9.2

2800

281°

101°

2800

101°

3.06°

TCH 31

5.7 NM

I-CFQ 0.8

VGSI and descent angles not coincident (VGSI Angle 4.00/TCH 31).

4001 x 100

1050 x 120

CATEGORY	A	B	C	D
S-10	1580-1	652 (700-1)	1580-1¾ 652 (700-1¾)	NA
CIRCLING	1580-1 652 (700-1)	1640-1 712 (800-1)	1660-2 732 (800-2)	NA

Detailed approach diagram for RWY 10:

- Altitudes: 928, 101°.
- Angles: 101°.
- Distances: 4001 x 100, 1050 x 120.
- Obstacles: Obstacle at 1050 x 120.

MIDDLETON, WISCONSIN
Amdt 1B 12AUG21

43°07'N-89°32'W

MIDDLETON MUNI/MOREY FLD (C29)
LOC/DME RWY 10