

WAAS Ch 42626 W23A	APP CRS 232°	Rwy Ldg TDZE 568 Apt Elev 577
--	------------------------	---


RNAV (GPS) RWY 23
KYLE-OAKLEY FLD (CEY)

⚠ DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA with Mayfield altimeter setting. When local altimeter setting not received use Mayfield altimeter setting: increase all DA/MDA 40 feet, and increase LPV, LNAV/VNAV all Cats, and LNAV Cats C and D visibility $\frac{1}{8}$ mile. For inop ODALS, increase LPV and LNAV/VNAV all Cats, and LNAV Cats C and D visibility $\frac{1}{4}$ mile. Helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F).

ODALS

MISSED APPROACH: Climb to 3000 direct EKACY and hold.

AWOS-3 119.975	MEMPHIS CENTER 133.65 292.15	UNICOM 122.7 (CTAF)
--------------------------	--	-------------------------------



ELEV 577 TDZE 568

MIRL Rwy 5-23
REIL Rwy 5

3000	EKACY	VGSI and RNAV glidepath not coincident (VGSI Angle 3.50/TCH 38).		4 NM Holding Pattern
*LNAV only.		AZCUF	GELME	
RW23		2100	232°	3000
1 NM		3.7 NM	6.8 NM	GP 3.00° TCH 40
CATEGORY	A	B	C	D
LPV DA	859- $\frac{7}{8}$		291 (300- $\frac{7}{8}$)	
LNAV/VNAV DA	861- $\frac{7}{8}$		293 (300- $\frac{7}{8}$)	
LNAV MDA	980- $\frac{3}{4}$	412 (500- $\frac{3}{4}$)	980-1	412 (500-1)
CIRCLING	1000-1 423 (500-1)	1040-1 463 (500-1)	1040-1 $\frac{1}{2}$ 463 (500-1 $\frac{1}{2}$)	1180-2 603 (700-2)

SE-1, 01 OCT 2026 to 29 OCT 2026

SE-1, 01 OCT 2026 to 29 OCT 2026