

WAAS CH 58011 W18A	APP CRS 180°	Rwy Ldg 3998 TDZE 83 Apt Elev 83
--	------------------------	---

RNAV (GPS) RWY 18
JOHN H HOOKS JR MEML (M79)

RNP APCH - GPS.

NA

Rwy 18 helicopter visibility reduction below 1 SM NA. Straight-in and Circling Rwy 18 NA at night. Use Monroe altimeter setting, when not received, use Bastrop altimeter setting and increase all DA/MDA 20 feet; increase LPV all Cats visibility 1/8 SM. Baro-VNAV NA.

MISSED APPROACH:
Climb to 1600 direct
APERE and hold.

MLU ASOS
125.05

MONROE APP CON ★
126.9

UNICOM
122.8 (CTAF) **0**

4 NM

HOLD 6000 1700

360°

180°

(IF/IAF)
OGELS

1600

180°

(6.9)

(FAF)
YIGLU

ZAPOR
1.3 NM to
RW18

187±

RW18

30 NM to OGELS (NoPT)

9 NM 2200

1700

090°

270°

OGELS

9 NM 2200

30 NM to OGELS

MISSED APCH FIX

APERE

360°

180°

4 NM

1600

APERE

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 50).

4 NM Holding Pattern

360°

180°

6000

1700

GP 3.60°

TCH 59

YIGLU

1600

ZAPOR

1.3 NM to
RW18

620*

1600

1.3 NM

2.5 NM

6.9 NM

CATEGORY	A	B	C	D
LPV DA	448-1	365 (400-1)	NA	NA
LNAV/VNAV DA	559-1 3/8	476 (500-1 3/8)	NA	NA
LNAV MDA	480-1	397 (400-1)	NA	NA
CIRCLING	600-1	517 (600-1)	NA	NA

ELEV 83

TDZE 83

180°

81

5.7 X 36

3998 X 17

REIL Rwy 18 and 36

MIRL Rwy 18-36

SC-4, 01 OCT 2026 to 29 OCT 2026

SC-4, 01 OCT 2026 to 29 OCT 2026

RAYVILLE, LOUISIANA
Amdt 1C 29DEC22

32°29'N-91°46'W

JOHN H HOOKS JR MEML (M79)
RNAV (GPS) RWY 18