RNAV (GPS) RWY 35

RUSK COUNTY (RFI)

WAAS	APP CRS	Rwy Ldg	4005
CH 86847	347°	TDZE	442
W35A		Apt Elev	442

RNP APCH - GPS.

Baro-VNAV and VDP NA when using GGG altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Rwy 35 helicopter visibility reduction below ¾ SM NA. Circling Rwy 12, 17 and 30 NA at night. When local altimeter setting not received, use GGG altimeter setting and increase LPV DA to 740 feet; increase LNAV/VNAV DA to 904 feet and all visibilities ¼ SM. Increase all MDAs 60 feet and LNAV visibility Cat C ¼ SM, and Circling visibility Cat C ¼ SM.

MISSED APPROACH: Climb to 900 then climbing left turn to 3000 direct ZIDAV and hold.

AWOS-3	LONGVIEW APP CON ★	UNICOM
119.375	124.275 257.975	122.8 (CTAF)







CATEGORY	A	B	C	D
LPV DA	692-1 250 (300-1)			NA
LNAV/VNAV DA	856-1⅛ 414 (500-1⅛)			NA
LNAV MDA	840-1 398 (400-1)		840-1⅛ 398 (400-1⅛)	NA
CIRCLING	920-1 478 (500-1)	960-1 518 (600-1)	1200-2¼ 758 (800-2¼)	NA

SC-2, 01 OCT 2026 to 29 OCT 2026
SC-2, 01 OCT 2026 to 29 OCT 2026