

WAAS CH 81836 W05A	APP CRS 054°	Rwy Ldg TDZE 255 Apt Elev 270
--	------------------------	---

RNAV (GPS) RWY 5

COLUMBIA/MARION COUNTY (ØRØ)

RNP APCH - GPS.


▼

NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.
When local altimeter setting not received, use Hattiesburgh/Laurel Rgnl altimeter setting and increase all DA 66 feet and all MDA 80 feet; increase LPV all Cats visibility 1/8 mile and LNAV/VNAV all Cats and Circling Cat C visibilities 1/4 mile, increase Circling Cat D visibility 1/2 mile, increase LNAV Cat C and D visibility 3/8 mile. VDP and Baro-VNAV NA when using Hattiesburgh/Laurel Rgnl altimeter setting. Rwy 5 helicopter visibility reduction below 3/4 SM NA.

MISSED APPROACH:
Climb to 2400 direct
NERAE and hold.

AWOS-3PT 120.675	HOUSTON CENTER 126.8 327.8	UNICOM 122.8 (CTAF)Ø
----------------------------	--------------------------------------	--------------------------------



ELEV 270		TDZE 255	
4 NM Holding Pattern		2400 NERAE	
2400 ← 234° 054° →		*NAV only.	
GP 3.00° TCH 40		1500	
6.1 NM		1.8 NM	
CATEGORY	A	B	C
LPV DA	505-7/8		250 (300-7/8)
LNAV/VNAV DA	743-1 5/8		488 (500-1%)
LNAV MDA	760-1	505 (500-1)	760-1 3/8 505 (500-1%)
CIRCLING	760-1 490 (500-1)	820-1 550 (600-1)	920-1 3/4 650 (700-1 3/4) 1000-2 1/4 730 (800-2 1/4)
REIL Rwy 5 and 23Ø MIRL Rwy 5-23Ø			