WAAS	APP CRS	Rwy Idg	5105
CH 90527	229°	TDZE	26
W23A		Apt Elev	26

RNAV (GPS) RWY 23


CAPE FEAR RGNL JETPORT/HOWIE FRANKLIN FLD (SUT)


RNP APCH - GPS.


Baro-VNAV NA when using Wilmington altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Wilmington altimeter setting and increase LPV DA to 335 feet, increase LNAV/VNAV DA to 327 feet, increase all MDAs 60 feet and Circling visibility Cat C ¼ SM. Rwy 23 helicopter visibility reduction below ¾ SM NA. VDP NA when using Wilmington altimeter setting.

MISSED APPROACH: Climb to 500 then climbing right turn to 3000 direct SWICK and hold.

AWOS-3P	WILMINGTON APP CON ★	UNICOM
124.175	118.25 284.65	123.05(CTAF) L







CATEGORY	A	B	C	D
LPV DA	284-1	258 (300-1)		NA
LNAV/VNAV DA	276-1	250 (300-1)		NA
LNAV MDA	480-1 454 (500-1)		480-1⅜ 454 (500-1⅜)	NA
CIRCLING	480-1 454 (500-1)	520-1 494 (500-1)	720-2 694 (700-2)	NA

SE-2, 01 OCT 2026 to 29 OCT 2026