

WAAS CH 87102 W18A	APP CRS 179°	Rwy Ldg TDZE 576 Apt Elev 589	RNAV (GPS) RWY 18 MCKINNEY NTL (TKI)	
--	------------------------	---	---	--

⚠


DME/DME RNP-0.3 NA. VDP NA with Dallas Love Fld altimeter setting. When local altimeter setting not received, use Dallas Love Fld altimeter setting and increase all DA 70 feet and all MDA 80 feet, increase LNAV Cats C and D ½ mile, and Circling Cats C and D visibility ½ mile. For inop MALSR when using Dallas Love Fld altimeter setting increase LPV all Cats visibility to 1 mile.


MALSR



MISSED APPROACH:
Climb to 3000 direct ONEME and hold.

ATIS 119.925	LONE STAR APP CON 124.3 282.275	MC KINNEY TOWER ★ 118.825 (CTAF) 0	GND CON 121.875	CLNC DEL 121.35 (When twr closed)	UNICOM 122.95
------------------------	---	---	---------------------------	--	-------------------------



 TWR ☆ 7002 X 150 36 (A4) HIRL Rwy 18-36 ①	3000 ↑ ONEME ✦ *LNAV only. LIRNE 2.5 NM to RW18 *0.9 NM to RW18 RW18 IKOTY 2300 1420* 2300 179° VELCI 3000 GP 3.00° TCH 50 0.9 NM 1.6 NM 2.8 NM 6 NM					
	CATEGORY	A		B	C	D
	LPV DA	776-½ 200 (200-½)				
	LNAV MDA	920-½ 344 (400-½)		920-⅝ 344 (400-⅝)		
	CIRCLING	1040-1 451 (500-1)		1120-1 531 (600-1)		1200-1¾ 611 (700-1¾) 1380-2½ 791 (800-2½)