

WAAS CH 78034 W30A	APP CRS 304°	Rwy Ldg TDZE Apt Elev	5499 247 247
--	------------------------	-----------------------------	---


RNAV (GPS) RWY 30

JOHN BELL WILLIAMS (JVW)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Circling NA for Cat D southwest of Rwy 12-30. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Hawkins Fld altimeter setting increase all DA/MDA 40 feet, increase LPV and LNAV/VNAV all Cats visibility and LNAV Cat C/D visibility ⅓ mile, increase Circling Cat C visibility ¼ mile. Baro-VNAV and VDP NA when using Hawkins Fld altimeter setting.

MISSED APPROACH:
Climb to 2900 direct
CIGDA and hold.

AWOS-3PT 118.675	JACKSON APP CON★ 125.25 319.2	UNICOM 123.0 (CTAF)
----------------------------	---	-------------------------------



ELEV 247	TDZE 247	2900	CIGDA	VGSI and RNAV glidepath not coincident (VGSI Angle 4.00/TCH 50).	4 NM Holding Pattern
*LNAV only RAYRO 2.7 NM to RW30 BOYAS 1900 DASLE 1 NM 1.7 NM 2.3 NM 6.9 NM					
CATEGORY		A	B	C	D
LPV DA		513-7⁄8 266 (300-7⁄8)			
LNAV/VNAV DA		699-1½ 452 (500-1½)			
LNAV MDA		740-1	493 (500-1)	740-1¾	493 (500-1¾)
CIRCLING		740-1 493 (500-1)	760-1 513 (600-1)	980-2 733 (800-2)	980-2¼ 733 (800-2¼)