

WAAS CH 99503 W27A	APP CRS 270°	Rwy Ldg TDZE 17 Apt Elev 17
--	------------------------	---

RNAV (GPS) RWY 27

GULF SHORES INTL/JACK EDWARDS FLD (JKA)

▼


▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Pensacola Intl altimeter setting. Circling Rwy 17, 35 NA at night. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Pensacola Intl altimeter setting and increase LPV DA to 295 feet; increase LNAV/VNAV DA to 559 feet and all visibilities ¼ SM; increase all MDAs 80 feet and visibility Cats C and D ¼ SM. For inop ALS, increase LNAV Cat C/D visibility to 1½ SM. For inop ALS, when using Pensacola Intl altimeter setting minimums, increase LPV all Cats visibility to ¾ SM, increase LNAV Cats C/D visibility to 1¾ SM.

MALSR

MISSED APPROACH:
Climb to 2500 direct
VUSRY and hold.

ATIS 134.525	PENSACOLA APP CON 120.65 270.8	GULF SHORES TOWER ★ 118.65 (CTAF) 0	GND CON 121.7	UNICOM 122.7
------------------------	--	---	-------------------------	------------------------



ELEV 17

D

TDZE 17

MIRL Rwy 17-35 0
HIRL Rwy 9-27 0

2500	VUSRY	JUDGE 2.4 NM to RWY 27	ORAXE 1.6 NM to RWY 27	WARLY 4 NM Holding Pattern
*RNAV only.		*1.1 NM to RWY 27	*820	GP 3.00° TCH 47
1.1	1.3	2.4 NM	6.2 NM	
CATEGORY	A	B	C	D
LPV DA	217-½ 200 (200-½)			
LNAV/VNAV DA	481-1½ 464 (500-1½)			
LNAV MDA	420-½ 403 (500-½)		420-¾ 403 (500-¾)	
CIRCLING	480-1 463 (500-1)		740-2 723 (800-2) 740-2¼ 723 (800-2¼)	

SE-4, 01 OCT 2026 to 29 OCT 2026

SE-4, 01 OCT 2026 to 29 OCT 2026