

WAAS CH 53714 W16A	APP CRS 159°	Rwy Ldg TDZE 2160 Apt Elev 2160
--	------------------------	---

RNAV (GPS) RWY 16

PIONEER VILLAGE FLD (ØV3)

Baro-VNAV NA. DME/DME RNP-0.3 NA. Use Kearney altimeter setting; when not received, use Holdrege altimeter setting and increase all DA 29 feet and all MDA 40 feet, increase LPV all Cats visibility ¼ mile. Circling NA to Rwy 5/23.

NA

MISSED APPROACH: Climb to 3700 direct MEDOC and hold.

EAR AWOS-3PT 123.875	MINNEAPOLIS CENTER 119.4 278.8	UNICOM 122.7 (CTAF) Ø
--------------------------------	--	---------------------------------

The main chart displays the RNAV (GPS) RWY 16 approach. Key features include:

- SPRIT** (VORTAC) at 4300 ft, 051° (22.9) NM.
- SUFBA** (IFAF) at 4300 ft, 069° (5) NM.
- CIBSA** (IF/IAF) at 4300 ft, 249° (5) NM.
- HENBA** (IAF) at 4300 ft, 279° (6.7) NM.
- MORGS** (IFAF) at 4300 ft, 279° (6.7) NM.
- FINVO** (FAF) at 2294 ft ±.
- RW16** at 2269 ft ±.
- MSA RW 16 25 NM** with a 4500 ft MSL.
- MISSED APCH FIX** at MEDOC, 3700 ft, 159°/339°.

ELEV 2160	TDZE 2160
------------------	------------------

This inset chart shows the location of MINDEN, NEBRASKA and the MRL Rwy 16-34. It includes a diagram of the runway layout with dimensions: 1275 x 300, 3900 x 60, and 34. The chart also shows the 159° heading and the 91° heading.

5 NM Holding Pattern				3700	MEDOC
4300 ← 339° 159° →				FINVO	RW16
GP 3.00° TCH 40				3500	
				6.1 NM	4.1 NM
CATEGORY	A	B	C	D	
LPV DA	2445-1	285 (300-1)	NA		
LNAV/VNAV DA	2574-1½	414 (500-1½)	NA		
LNAV MDA	2580-1	420 (500-1)	NA		
CIRCLING	2680-1 520 (600-1)	2780-1 620 (700-1)	NA		

MINDEN, NEBRASKA

Orig-B 02JAN20

40°31'N-98°57'W

PIONEER VILLAGE FLD (ØV3)

RNAV (GPS) RWY 16