

WAAS CH 82518 W35A	APP CRS 354°	Rwy Idg TDZE Apt Elev	3898 822 825
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 35
HUTSON FLD (GAF)

RNP APCH - GPS.


▽ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Grand Forks Intl altimeter setting: increase LPV DA to 1141 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 1268 feet and all visibilities ¼ SM; increase all MDA's 80 feet and visibility circling Cat C ¼ SM. Baro-VNAV NA when using Grand Forks Intl altimeter setting.

▲ NA Circling NA to Rwys 8 and 26.

MISSED APPROACH: Climb to 4000 direct OHUTO and hold, continue climb-in-hold to 4000.


AWOS-3
118.625

GRAND FORKS APP CON★
118.1 318.1

UN|COM
122.8 (CTAF) **L**


ELEV 825

TDZE 822



4000	OHUTO
	

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 26).

4 NM
Holding Pattern

CATEGORY	A	B	C	D
LPV DA	1072-1	250 (300-1)		NA
LNAV/ VNAV DA	1199-1¼	377 (400-1¼)		NA
LNAV MDA	1180-1	358 (400-1)		NA
CIRCLING	1340-1	515 (600-1)	1440-1¾ 615 (700-1¾)	NA

GRAFTON, NORTH DAKOTA
Orig-A 03NOV22

48° 24'N-97° 22'W

HUTSON FLD (GAF)
RNAV (GPS) RWY 35