



APP CRS 173°	Rwy Ldg	12000
	TDZE	5339
	Apt Elev	5434

RNAV (RNP) Z RWY 17L

DENVER INTL (DEN)

RNP AR APCH - GPS, min RNP 0.90. Authorization required.		MALSR 	MISSED APPROACH: Climb to 5900, then climbing left turn to 10000 direct UYOZY and track 128° to YEBUV and track 078° to LIMEX and hold.
	For uncompensated Baro-VNAV systems, procedure NA below -26°C or above 54°C. Simultaneous approach authorized. For inop ALS, increase RNP 0.10 all Cats visibility to RVR 4500 and RNP 0.30 all Cats visibility to RVR 5500.		

D-ATIS 125.6 379.9	DENVER APP CON 119.3 307.3 (N) 120.35 379.3 (S)	DENVER TOWER 132.35 239.275	GND CON 121.35 379.175 (W) 121.85 377.1 (E)
------------------------------	---	---------------------------------------	---



5900	10000	UYOZY	tr 128°	YEBUV	tr 078°	LIMEX	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 66). GWENS	
							9000	
							GP 3.00° TCH 55	
CATEGORY	A		B		C		D	
RNP 0.10 DA			5600/24		261 (200-½)			
RNP 0.30 DA			5716/35		377 (300-⅔)			
AUTHORIZATION REQUIRED								