


WAAS CH 48909 W21A	APP CRS 209°	Rwy Ldg 5498 TDZE 948 Apt Elev 948
--	------------------------	---

RNAV (GPS) Z RWY 21
GEORGETOWN-SCOTT COUNTY RGNL (27K)

V For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16° C (4° F) or above 46° C (114° F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Lexington altimeter setting and increase LPV DA to 1186, LNAV/VNAV DA to 1460, and all MDA 40 feet; increase LPV all Cats and LNAV Cats C/D and Circling Cat D visibility ¼ SM. Baro-VNAV and VDP NA with Lexington altimeter setting.

MISSED APPROACH: Climb to 3000 direct YAPUT and right turn on track 301° to SOKOC and right turn on track 049° to GENUS and hold.

AWOS-3 119.975	LEXINGTON APP CON 120.15 259.3 (040°-220°) 120.75 298.9 (221°-039°)	CLNC DEL 127.425	UNICOM 123.0 (CTAF) 
--------------------------	--	----------------------------	---



ELEV 948

TDZE 948

209°

S498 X 100

0.3% UP

MIRL Rwy 3-21

REIL Rws 3 and 21

3000 ↑	YAPUT 	SOKOC tr 301°	GENUS tr 049°	
*LNAV only. CUDIG 1.9 NM to RW21 ETOXY 2500 OBUGE 4 NM Holding Pattern 029° → 3000 ← 209° GP 3.00° TCH 30 1.2 NM 0.7 NM 2.8 NM 6.1 NM				
CATEGORY	A	B	C	D
LPV DA	1148- $\frac{3}{4}$ 200 (200- $\frac{3}{4}$)			
LNAV/VNAV DA	1422-1 $\frac{3}{4}$ 474 (500-1 $\frac{3}{4}$)			
LNAV MDA	1360-1 412 (500-1)		1360-1 $\frac{1}{4}$ 412 (500-1 $\frac{1}{4}$)	
CIRCLING	1420-1 472 (500-1)		1560-1 $\frac{3}{4}$ 612 (700-1 $\frac{3}{4}$)	1660-2 $\frac{1}{4}$ 712 (800-2 $\frac{1}{4}$)