

WAAS
CH **97636**
W14A

APP CRS
148°

Rwy Ldg
TDZE
Apt Elev

3296
1242
1242

RNAV (GPS) RWY 14

SAUK CENTRE MUNI (D39)

RNP APCH - GPS.


▼

⚠

Baro-VNAV NA when using Glenwood altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. VDP NA with Glenwood altimeter setting. When local altimeter setting not received, use Glenwood altimeter setting and increase all DA/MDA 60 feet, increase LNAV/VNAV all Cals visibility ½ mile. Rwy 14 helicopter visibility reduction below ¾ SM NA. Circling NA to Rwy 8 and 26.

MISSED APPROACH:
Climb to 3000 direct
VOCAB and hold.

AWOS-3 118.475	MINNEAPOLIS CENTER 126.1 269.2	CTAF 122.90
--------------------------	--	-----------------------



4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 23).			
3000 ← 328°		ZERNU		YIKVU 2900	
GP 3.00° TCH 40		148°		WETUB 2.1 NM to RW14	
		2900		*1.3 NM to RW14	
		5.7 NM		*1940	
		3 NM		RW14	
		0.8 NM		1.3 NM	
CATEGORY		A	B	C	D
LPV DA		1492-1	250 (300-1)	NA	
LNAV/DA		1500-1	258 (300-1)	NA	
LNAV MDA		1680-1	438 (500-1)	NA	
CIRCLING		1700-1 458 (500-1)	1740-1 498 (500-1)	NA	